

## THE 4000 SERIES - DOUBLE HUNG



 **North  
East**  
WINDOWS USA, INC.

FAMILY MADE IN AMERICA SINCE 1947

# STANDARD FEATURES

- Replacement 3 1/4" Frame Depth
- Custom Sizing To The Nearest 1/4"
- Euro White, Almond, Bronze, Black, 2-Tone Lami Black
- Fusion Welded Frame & Sashes
- Maintenance Free Multi-Chambered Vinyl Profiles
- Built-In Water Weeping System
- Constant Steel Force Coil Balances
- Two Premium Night Latches
- One Piece Sloped Sill - No Weep Hole Covers!
- Positive Action Cam Lock & Keeper
- Dual Locks For Windows Wider Than 24"
- Heavy Duty Weatherstripping For Air & Water Performance
- Tilt-In & Removable Sashes For Easy Cleaning
- Snap-In Glazing Beads For Easy Glass Replacement
- 7/8" Overall Insulated Glass Unit
- High Performance Warm Edge Spacer System
- Fully Extruded Integral Heavy Duty Lift Handles
- Built In Jamb Adjusters For Easy Installation
- Pre-Drilled Pilot Holes For Easy Installation
- Head Expander & Adjustable Sill Angle
- Standard Half Screen - Roll Formed Aluminum Frame
- Fiberglass Screen Mesh
- Metal Reinforced Meeting Railings
- Accessory Grooves For Easy Zero Degree Mulling
- Continuous Frame For Mulled Units
- AAMA Gold Label Standard
- Limited Lifetime Warranty!



\*Optional Fiberglass Reinforcement & Foam Shown



**DH4000**  
**AVAILABLE OPTIONS**



WINDOW + DOOR  
**TOP 100**  
MANUFACTURERS



## NFRC RATINGS

| GLASS CONFIGURATION           | FOAM | U-FACTOR  | SHGC      | VT        |
|-------------------------------|------|-----------|-----------|-----------|
| CG70 (SS)/ARG90/CLEAR (SS)    | NO   | 0.28      | 0.26/0.24 | 0.52/0.46 |
| CG70 (DS)/ARG90/CLEAR (DS)    | NO   | 0.28      | 0.26/0.24 | 0.51/0.46 |
| CG70 (SS)/ARG90/CLEAR (SS)    | YES  | 0.26      | 0.26/0.24 | 0.52/0.46 |
| CG70 (DS)/ARG90/CLEAR (DS)    | YES  | 0.26      | 0.26/0.24 | 0.51/0.46 |
| E270 (DS)/ARG90/CS73P (DS)    | YES  | 0.23      | 0.26/0.23 | 0.50/0.44 |
| E180 (DS)/ARG90/CS73P (DS)    | YES  | 0.24      | 0.49/0.41 | 0.50/0.44 |
| CG70 (DS)/ARG90/LAMI 1/4" CLR | NO   | 0.27/0.27 | 0.26/0.24 | 0.50/0.45 |
| CG70 (DS)/ARG90/LAMI 1/4" CLR | YES  | 0.26/0.26 | 0.28/0.25 | 0.51/0.46 |

## MAKE SIZES

|                              |        |
|------------------------------|--------|
| MIN. WIDTH                   | 14"    |
| MAX. WIDTH                   | 48"    |
| MULLED UNIT REQUIRED W > 48" |        |
| MIN. HEIGHT                  | 28"    |
| MAX. HEIGHT                  | 90"    |
| TRANSOM REQUIRED H > 90"     |        |
| MIN. EGRESS W                | 37.25" |
| MIN. EGRESS H                | 63"    |

## AAMA RATINGS

|                          |                 |
|--------------------------|-----------------|
| Performance              | R-PG35          |
| With Metal Reinforcement | R-PG50          |
| Air                      | <.22 @ 1.57 PSF |
| Water Resistance         | 5.25 PSF        |
| Uniform Structural Load  | 50.25 PSF       |
| Uniform Design Load      | 35 PSF          |
| Forced Entry             | Grade 10        |
| Status                   | Gold Label      |