

THE DH990 SERIES - DOUBLE HUNG



 **North
East**
WINDOWS USA, INC.

FAMILY MADE IN AMERICA SINCE 1947

STANDARD FEATURES

- New Construction 3 1/4" Frame Depth
- Custom Sizing To The Nearest 1/4"
- Euro White, Almond, Bronze, Black, 2-Tone Lami Black
- Fusion Welded Frame & Sashes
- Maintenance Free Multi-Chambered Vinyl Profiles
- Built-In Water Weeping System
- Constant Steel Force Coil Balances
- Two Premium Night Latches
- Snap In Sloped Sill
- Positive Action Cam Lock & Keeper
- Dual Locks For Windows Wider Than 24"
- Heavy Duty Weatherstripping For Air & Water Performance
- Tilt-In & Removable Sashes For Easy Cleaning
- Snap-In Glazing Beads For Easy Glass Replacement
- 7/8" Overall Insulated Glass Unit
- High Performance Warm Edge Spacer System
- Fully Extruded Integral Heavy Duty Lift Handles
- Built In Jamb Adjusters For Easy Installation
- Pre-Drilled Pilot Holes For Easy Installation
- Head Expander & Adjustable Sill Angle
- Standard Half Screen - Roll Formed Aluminum Frame
- Fiberglass Screen Mesh
- Metal Reinforced Meeting Railings
- Accessory Grooves For Easy Zero Degree Mulling
- Continuous Frame For Muller Units
- AAMA Gold Label Standard
- Limited Lifetime Warranty!



WINDOW + DOOR
TOP 100
MANUFACTURERS



NFRC RATINGS

GLASS CONFIGURATION	FOAM	U-FACTOR	SHGC	VT
CLEAR (SS)/AIR/CLEAR (SS)	NO	0.45	0.57/0.51	0.60/0.53
CLEAR (DS)/AIR/CLEAR (DS)	NO	0.45	0.56/0.50	0.59/0.53
E270 LOWE (SS)/ARG90/CLEAR (SS)	NO	0.29	0.27/0.24	0.51/0.45
E270 LOWE (DS)/ARG90/CLEAR (DS)	NO	0.29	0.27/0.24	0.50/0.45
E270 LOWE (SS)/ARG90/CLEAR (SS)	YES	0.27	0.27/0.24	0.51/0.45
E270 LOWE (DS)/ARG90/CLEAR (DS)	YES	0.27	0.27/0.24	0.50/0.45
E270 LOWE (DS)/ARG90/CS73P (DS)	YES	0.24	0.25/0.23	0.47/0.42
E180 LOWE (DS)/ARG90/CS73P (DS)	YES	0.24	0.44/0.39	0.53/0.47

MAKE SIZES

MIN. WIDTH	18"
MAX. WIDTH	48"
MULLED UNIT REQUIRED W > 48"	
MIN. HEIGHT	28"
MAX. HEIGHT	90"
TRANSOM REQUIRED H > 90"	
MIN. EGRESS W	36"
MIN. EGRESS H	62.5"

AAMA RATINGS

Performance	R-PG35
With Metal Reinforcement	R-PG50
Air	<.05 @ 1.57 PSF
Water Resistance	7.52 PSF
Uniform Structural Load	75 PSF
Uniform Design Load	50 PSF
Forced Entry	Grade 10
Status	Gold Label

DH990
AVAILABLE OPTIONS